

PAINT PROCESS

LaForce can **paint doors and frames prior to delivery**, which guarantees quality, streamlines the construction process, and ensures a consistent color match with building components!



THE LAFORCE PAINT PROCESS IN SIX STEPS

- 1 Prime and sand**
- 2 Wipe down with wax and grease remover**
This is completed just prior to entering the paint booth, to provide absolute cleanliness.
- 3 Hang on specialized, wheeled racking**
This provides the ability to spray the entire piece at one time for best coverage and consistency.
- 4 Paint with urethane based-paint**
This features a customized sheen that is between a "satin" and a "flat" finish. The paint is also mixed with a urethane hardener (speeds the drying process) and slow reducer (allows the use of a paint spray gun.)
- 5 Bake for 25 minutes at 140-170° F**
- 6 Securely palletize for shipment or installation**
This includes using foam blocks for protection, banding so material does not shift in transit, and wrapping for a final protection.

WHAT ARE THE BENEFITS OF USING LAFORCE'S PAINT PROCESS?

Our paint staff is highly trained, skilled, and take great pride in their work. No product leaves the paint booth unless it can confidently adhere to LaForce quality standards. We are pleased to provide a high-quality product, thanks to our meticulous paint process!

CONTACT US

Phone: 1.800.236.8858

Website: www.laforceinc.com

Social Media: [f](#) [blog](#) [g+](#) [in](#) [You Tube](#) [p](#) [t](#)